



Installation Instructions

Exhaust Cutout Kits

429200, 429201, 429225, 429226, 429250, 429251, 429300, 429301

Parts included:

Dual Kits Include:

- 2 - Y-Pipes
- 2 - Valve/Motor Assemblies
- 2 - Dump Flanges
- 2 - Dump Pipes
- 2 - V-Band Clamps
- 4 - Gaskets
- 1 - Remote Keyfob
- 1 - Wiring Harness

Single Kits Include:

- 1 - Y-Pipe
- 1 - Valve/Motor Assembly
- 1 - Dump Flange
- 1 - Dump Pipe
- 1 - V-Band Clamp
- 2 - Gaskets
- 1 - Remote Keyfob
- 1 - Wiring Harness

Please read these instructions before installing! WARNING! Exhaust cutouts are NOT street legal. Exhaust cutouts are for offroad and drag racing only.

Do not install on vehicles with catalytic converters. Possible damage to the valve can occur from the excessive heat and will automatically void the warranty.

All Performance World exhaust cutout kits come complete with the necessary parts for installation. Install before the mufflers, closer to the header collector or in the best location for your application. Install each motor/valve assembly with the motor either horizontal or pointing upwards to avoid damage over speed bumps etc.

Wiring: The Performance World exhaust cutouts are designed for an easy installation. Simply route the pre-terminated wiring from the cutout(s) into the vehicle taking care to fasten away from hot exhaust, driveshaft and sharp edges. Mount the control box in a suitable location close to the 12V lighter receptacle. Connect the male/female plugs and plug into the lighter. Start vehicle and test operation. Re-tighten all hardware as required after 50-100km.

NOTE: If you wish to have the cutouts activated by a manual switch, a switch/control box is available separately #PER429000



Performance World warrants the exhaust cutouts for one (1) year from date of original purchase. Warranty does not cover damaged or modified components. Warranty replacement will be for the defective component ONLY and NOT the entire kit. (eg. valve assembly)